

## Worldwide 60 m Frequency Chart

5250	5260	5270	5280	5290	5300	5310	5320	5330	5340	5350	5360	5370	5380	5390	5400	5410	
← Entire band 5260 kHz to ...						CW	QRP				DIGITAL	USB	PHONE to 5410 kHz →			Norway (LA, LB, JW, JX, 3Y) 5260 -5410; Denmark 5260 - 5450	
← Entire band 5250 to 5310 kHz →																	Bangladesh 5250 - 5310
								5330.5									USA 5 channels
	5258.5	5258.5										5366.5	5366.5				U.K. 7 channels
	5267.5											5371.5	5371.5				Canada 7 channels Experimental
			5278.5														Iceland 8 channels
	5288.5		5288.5					5330.5				5366.5	5366.5				Greenland 6 channels
			5298.6									5371.5	5371.5				Finland 8 channels
								5330.6				5366.6	5366.6				New Zealand 2 channels
								5320.0				5346.6	5346.6				St. Lucia + other countries 5 channels
								5330.5				5366.5	5366.5				
												5371.5	5371.5				
														5395.0			
															5403.5		

**Dial Frequency:**

Above listed channel frequencies are "dial frequencies" as you see them on your radio.  
 The center-of-channel offset is already figured out for you.  
 (The center-of-channel is usually 1.5 kHz higher than the dial frequency).  
 The band edge frequencies are NOT dial frequencies. No emissions shall occur outside band edges!

**Emissions Modes:**

The current worldwide standard for Amateur Radio on 5 MHz is **Upper Sideband (USB)**.  
 Other emission types are also in use. No bandwidth should exceed 2.7 kHz for all modes.

**Beacons:**

5290 kHz - U.K. - 3 beacons (GB3ORK, GB3RAL, GB3WES).  
 5195 kHz - Germany - DRAS.

The following commercial services may be used as beacons:

- 5000.0 kHz - WWV - Fort Collins, Colorado; 10 kW
- 5000.0 kHz - WWVH - Kauai, Hawaii; 10 kW
- 5446.5 kHz - AFRTS - Florida Keys; USB
- 5450.0 kHz - VOLMET RAF - UK; 10 kW USB
- 5505.0 kHz - VOLMET - Shannon, Ireland; 3 kW USB

**Emergency channels:**

Australia -WIA has permission to use 5102 kHz and 5355 kHz for emergency communications.  
 Alaska - 5167.5 kHz used for emergency communications.

**NRRL Norwegian Proposed Activity Centers - NOTE that primary users have priority vs. amateur radio:**

- CW: 5310 kHz (5305 - 5315 kHz)
- DIGITAL: 5355 kHz (5350 - 5360 kHz)
- USB: 5375 kHz (5375 - 5394 kHz)

- QRP: 5335 kHz (5335 - 5340 kHz)
- INT CALL: 5403.5 kHz (International Calling Channel)

Norwegian - Norwegian VFO QSOs should NOT be made on the international frequency channels, and should be held at frequencies with interference-free distance to such channels and other users.

Please send updates and corrections to [la8oka@Tarril.net](mailto:la8oka@Tarril.net)